

➔ Power distribution units with direct power feeding

Reference	Designation	Nb of socket outlets	Length (mm)
620035	Direct power feeding	3	176
620036	Direct power feeding	4	220
620042	Direct power feeding	6	308
620100	Direct power feeding	7	352
620001*	Direct power feeding	9	440
620101	Direct power feeding	7	704
620102	Direct power feeding	10	968
620103	Direct power feeding	13	1232
620104	Direct power feeding	19	1760

Over 440 mm length the listed product offer a 44 mm space plate between the socket-outlets.

* 1U-19" standard.



➔ Power distribution units with double pole switch with light indicator

Reference	Designation	Nb of socket outlets	Length (mm)
620105	Double pole switch	3	220
620106	Double pole switch	5	308
620107	Double pole switch	6	352
620017*	Double pole switch	8	440
620093	Double pole switch	7	704
620094	Double pole switch	10	968
620108	Double pole switch	13	1232
620109	Double pole switch	19	1760

Over 440 mm length the listed product offer a 44 mm space plate between the socket-outlets.

* 1U-19" standard.



■ DESCRIPTION

Power distribution unit : Natural anodized aluminium body with a width of 44 mm (1U)

Supply : HO5VVF. 3 G 1,5 mm² cable - 2 m with a mixed french/german moulded plug 16A - 250V

End-caps : 1 grey end-cap with cord-clamp and 1 grey smooth end-cap

Socket-outlets : Germans, grey, 2 P + E 10/16A - 250V with contact shutters

Individual packaging

Mounting brackets supplied